

TANK FOAMER 130 L

Foam Applicators. Thanks to the integrated pump powered by compressed air, Unidoz Tank Foamer units produce dense and well-aerated foam. The device uses pre-mixed chemicals from the tank. Ejects foam through the discharge hose and the fan nozzle. Providing a high degree of coverage of the foamed surface.

OVERVIEW

- PRODUCT CODE : **TS130**
- CAPACITIES : **130 L**
- POWER SUPPLY : **Air pressure**
- AIR PRESSURE REQUIREMENTS : **3-6 bar with 145 to 285 l/min**
- DISCHARGE HOSE LENGTH : **5/10/15/20 m**
- LANCE LENGTH : **50 cm**
- LIQUID TEMPERATURE : **Min 5°C, max 40°C**
- FOAM OUTPUT : **60 to 170 liters/minutes**
- FOAM DISTANCE : **30° nozzle; 70cm-100cm
No nozzle; 3m-5m**
- PUMP SEALS : **Santoprene, Viton**
- ALLOWED FLUIDS : **SANTOPRENE : Acids Alkaline, Soaps, Alcohol, Ketones, Potable Water
VITON : Oils, Solvents, D-Limonene, Aromatic & Halogenated Hydrocarbons, Acids**
- WHEEL TYPE : **Non-marking wheels or Food approved poliamid**
- WEIGHT : **26 kg**



Pallet Load

- PACKAGE SIZE: **570 x 870 x 570 mm**
- PALLET: **1200 x 1000mm**
- N PACKAGES: **6**
- N LAYERS: **3**
- SURFACE USAGE: **82.7%**
- VOLUME USAGE: **74.4%**
- TOTAL WEIGHT: **78 KG**

