

TANK FOAMER 200L

Foam Applicators. Thanks to the integrated pump powered by compressed air, Unidoz Tank Foamer units produce dense and well-aerated foam. The device uses pre-mixed chemicals from the tank. Ejects foam through the discharge hose and the fan nozzle. Providing a high degree of coverage of the foamed surface.



OVERVIEW

- PRODUCT CODE : TF200
- CAPACITIES : 200 L
- POWER SUPPLY : Air pressure
- AIR PRESSURE REQUIREMENTS : 3- 6 bar with 145 to 285 l/min
- DISCHARGE HOSE LENGTH : 5/10/15/20 m
- LANCE LENGTH : 50 cm
- LIQUID TEMPERATURE : Min 5°C, max 40°C
- FOAM OUTPUT : 60 to 170 liters/minutes
- FOAM DISTANCES : 30° nozzle; 70 cm – 100cm; no nozzle; 3 m -5m
- PUMP SEALS : Santoprene, Viton
- ALLOWED FLUIDS : SANTOPRENE - Acids Alkaline, Soaps, Alcohol, Ketones, Potable Water; VITON - Oils, Solvents, D-Limonene, Aromatic & Halogenated Hydrocarbons, Acids
- WHEEL TYPE : Non-marking wheels or Food approved poliamid
- WEIGHT : 29 kg

Pallet Load

- PACKAGE SIZE: 570 x 840 x 770 mm
- PALLET: 1200 x 1000mm
- N PACKAGES: 4
- N LAYERS: 2
- SURFACE USAGE: 79.8%
- VOLUME USAGE: 72.3%
- TOTAL WEIGHT: 60 KG

